
PHF TB1108X14MM



Bushing no. TB1108 d = Bore diameter (mm) 14 Bore diameter (in) 0.55 Keyway width (mm) 5 Keyway depth (mm) 2.3 (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (in) - Weight (kg) 0.14 Weight (lbs) 0.31		
(mm) Bore diameter (in) 0.55 Keyway width (mm) 5 Keyway width (in) 0.2 Keyway depth (mm) 2.3 (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	Bushing no.	TB1108
Bore diameter (in) 0.55 Keyway width (mm) 5 Keyway width (in) 0.2 Keyway depth (mm) 2.3 (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	d = Bore diameter	14
Keyway width (mm) 5 Keyway width (in) 0.2 Keyway depth (mm) 2.3 (mm) 0.09 A (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	(mm)	
(mm) 0.2 Keyway width (in) 0.2 Keyway depth (mm) 2.3 (mm) 0.09 A (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	Bore diameter (in)	0.55
Keyway width (in) 0.2 Keyway depth (mm) 2.3 Keyway depth (in) 0.09 A (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	Keyway width	5
Keyway depth (mm) 2.3 Keyway depth (in) 0.09 A (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	(mm)	
(mm) Keyway depth (in) 0.09 A (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	Keyway width (in)	0.2
Keyway depth (in) 0.09 A (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	Keyway depth	2.3
A (mm) 38.4 A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	(mm)	
A (in) 1.51 B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	Keyway depth (in)	0.09
B (mm) 22.2 B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	A (mm)	38.4
B (in) 0.87 D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	A (in)	1.51
D (mm) 36.9 D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	B (mm)	22.2
D (in) 1.45 E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	B (in)	0.87
E (mm) - E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	D (mm)	36.9
E (in) - F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	D (in)	1.45
F (mm) 6.350 x 12.700 F (in) - Weight (kg) 0.14	E (mm)	-
F (in) - Weight (kg) 0.14	E (in)	-
Weight (kg) 0.14	F (mm)	6.350 x 12.700
1. c.B., ()	F (in)	-
Weight (lbs) 0.31	Weight (kg)	0.14
	Weight (lbs)	0.31

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



[®] SKF is a registered trademark of the SKF Group

[©] SKF Group 2012