

Datasheet **FLENDER couplings N-EUPEX H 140**

Design according to brochure: FLE10.2

Ordering Data **2LC0170-6AG11-0AC0-Z**
 B28



Client-Order-No:
 Order-No:
 Quotation-No: **QTZ114058-1A**
S180 UNBORED

Item-No: **100**
 Consignment-No:
 Project: **SPOJKA N-EUPEX | N-EUPEX H140**

Coupling - Basic data

Product selection

[17]	Series:	N-EUPEX FLE10.2 2020.1
[AG]	Type:	H
[06]	Size:	140
[AG]	Scope of supply:	Complete coupling

Power data

Rated torque	500 Nm
Maximum speed	5800 rpm
Fatigue torque	-
Ambient temperature	-30...+80°C

Connection 1 Part 1

[1]	Hub variant:	Hub diameter: 100 mm, Without bore
-----	--------------	------------------------------------

Distance between shaft ends / Intermediate spacer length

[C]	Distance S:	S=180MM
-----	-------------	---------

Balancing

[STD]	Balancing quality:	Standard balancing
-------	--------------------	--------------------

Connection 2 Part 5

[1]	Hub variant:	Hub diameter: 100 mm, Without bore
-----	--------------	------------------------------------

Product specific options

[STD]	Conformity marking:	None
[STD]	Flexible element:	flexible elements NBR 80 Shore A

Corrosion protection

[B28]	Conservation:	Wax (TECTYL) - Indoor storage up to 36 months (suitable for sea freight)
[STD]	Paint coat:	No coating