


Upínací pouzdra CAL

Typ SIT-LOCK 9


CAL 9 / SIT-LOCK 9

Označení	Rozměry			Krouťicí moment	Axiální síla	Tlak na hřídel	Tlak na náboj	Upínací matice	
	d x D (mm)	D ₁ (mm)	H (mm)					B (mm)	M _t (Nm)
14 x 25	32	6,5	16,5	38	5,1	200	110	KM 4	95
15 x 25	32	6,5	16,4	41	5,5	185	110	KM 4	95
16 x 25	32	6,5	16,5	43	5,45	174	110	KM 4	95
17 x 26	32	6,5	16,5	47	5,5	164	107	KM 4	95
18 x 26	32	6,5	16,5	49	5,4	155	107	KM 4	95
19 x 30	38	6,5	18,0	62	6,6	176	112	KM 5	160
20 x 30	38	6,5	18,0	66	6,6	167	111	KM 5	160
22 x 32	38	6,5	18,0	73	6,6	152	105	KM 5	160
24 x 35	45	6,5	18,0	105	8,75	185	127	KM 6	220
25 x 35	45	6,5	18,0	110	8,8	178	127	KM 6	220
28 x 36	45	6,5	18,0	120	8,55	159	124	KM 6	220
30 x 40	52	7	19,5	160	10,6	164	123	KM 7	340
32 x 42	52	7	19,5	170	10,6	154	117	KM 7	340
35 x 45	58	8	21,5	230	13,1	153	120	KM 8	480
36 x 45	58	8	21,5	240	13,3	149	120	KM 8	480
38 x 48	58	8	21,5	250	13,1	141	112	KM 8	480
40 x 52	65	10	24,5	310	15,5	120	93	KM 9	680
42 x 55	65	10	25,5	320	15,2	114	87	KM 9	680
45 x 57	70	10	25,5	400	17,7	122	96	KM 10	870
48 x 62	75	10	25,5	500	20,8	135	105	KM 11	970
50 x 62	75	10	25,5	520	20,8	130	105	KM 11	970
55 x 68	80	12	27,5	610	22	103	84	KM 12	1100
56 x 68	80	12	27,5	620	22	101	82	KM 12	1100
60 x 73	85	12	28,5	800	26,6	113	93	KM 13	1300
63 x 79	92	14	30,5	980	31,1	107	86	KM 14	1600
65 x 79	92	14	30,5	1010	31	104	86	KM 14	1600
70 x 84	98	14	31,5	1240	35,4	110	92	KM 15	2000